

SALINITY PEN FOR SEA WATER

NEW

Changed to gray battery cap



8372S

Salinity Pen for Sea Water 8372S

- Big LCD with dual display to update measuring
- Auto ranging in high concentration solution
= => One display value in ppt scale or % or S.G. Not more ppm
- Calibration values are adjustable & calibration information can be reviewed
- Wider measuring range and more display unit:
8372: Salinity (~~ppm~~, ppt, %, specific gravity) & Temp.



IP65



Auto Power Off



Auto Temp. Compensation



Metric/Imperial




Low Battery



HOLD

Model	8372S	8372
Cond. range	N/A	N/A
Cond. accuracy	N/A	N/A
Cond. resolution	N/A	N/A
TDS range	N/A	N/A
TDS accuracy	N/A	N/A
TDS resolution	N/A	N/A
Salinity range	0.0-42.0 ppt or 0.0%-4.2% or 0.950-1.080(S.G) based on SEA WATER	0-9999ppm or 10.0-100.0 ppt or 0.0%-10.0% or 0.950-1.080(S.G) based on NaCl
Salinity accuracy	+/-1%F.S +/- 1 digit	+/-1%F.S +/- 1 digit
Salinity resolution	0.1 ppt or 0.1% or 0.001(S.G)	1ppm or 0.1 ppt or 0.1% or 0.001(S.G)
Temp. range		-5~60.0°C
Temp. accuracy		+/-0.5°C
Temp. resolution		0.1
ATC		ATC
TDS factor	Built-in SEA WATER conductivity to TDS conversion factor	Built-in NaCl conductivity to TDS conversion factor
LCD size		30(H)x18(W)mm
Operating temp.		0~50°C
Operating RH%		Humidity<80%
Storage temp.		0~60°C
Storage RH%		Humidity < 90%
Sensor life time		>6 months (with good maintenance)
Dimension		165(L)x35(W)x32(H)mm
Weight		115g
Battery		LR44 x 4pcs
Standard Package		Meter/Battery/Manual/Paper box

Salinity in specific gravity unit is good for artificially made sea water



Ordering Code
VZ8372AZS, 8372 Salinity pen for sea water