INDOOR AIR QUALITY DATALOGGER



Programmable air quality light bar indicator







For both Wall mount & Desktop



Ordering Code

VZ77294AZ, 77294 CO2 logger with light bar VB17729A, 5V USB adaptor with 4 plugs

CO₂, HUMIDITY, TEMPERATURE **DATALOGGER 77294**

- ■Large LED displays and record CO₂, Humidity and Temperature readings simultaneously
- ■12000 times auto logging. USB2.0 plug and play. No need to operate through specific software.
- ■Designed with high accuracy NDIR (non-dispersive infrared) waveguide technology CO2 sensor
- ■22cm long 3-color green, yellow and red LED light bar to indicate the CO2 concentration level
- ■ABC (automatic background calibration) preset on for long time drift compensation





















Model	77294
Measuring range	
CO2	0~9999 ppm, -10.0~60.0 [°] C (14~140 [°] F)
Temperature	
Humidity	0.1~99.9% RH
Resolution	1ppm , 0.1 ⁰ C/ ⁰ F, 1%RH
Accuracy	
CO2	<u>+</u> 50ppm <u>+</u> 5% of reading(0~2000ppm)
Temperature	Other range is 10% of reading ±0.6°C/±0.9°F
remperature	±5%RH (at 25°C, 10~90%RH);
Humidity	±7%RH (at 25°C, other range)
	in the state of th
Warm-up time	10 seconds
Response time	
CO2	<30 seconds(90% step change)
Tair	<2 mins (90% step change)
Humidity	<20 minutes (90% step change)
Auto Logging	12000 times records
IP rating	IP20
Operating condition	0~50°C, 0~95% RH (avoid condensation)
Storage condition	-20~ 50°C,0~95%RH(avoid condensation)
Power supply	5VDC USB type C port
Power consumption	<500mA
Meter size (LxWxH,mm)	226x 152 x 45
Weight	450g
Standard package	Meter, manual, Type C cable, Hanging accessories.

Areas of application: Widely used in the office building, school, exhibition hall, shopping mall, meeting room, fitness center, restaurant and other public places where energy bill, personal comfort and healthy are important.

